



LADDER CROSS-REFERENCE CATALOG



Grainger | Height | Model # Description

FIBERGLASS STEPLADDERS

		il IAA city: 375 lbs	7400 SERIES STEPLADDER Patented EDGE® bracing provides enhanced bottom bracing protection against damage. Aluminum external rail shields to the bottom. Full set of large heavy duty aluminum knee rear horizontals. Heavy-duty aluminum Tool-Tra-Top® seculnternal spreader bars.	provide additional reinforcemer braces on all front steps and all
4XN71	4 FT	Werner 7404	Ladder Height 4', Approx. Shipping Weight 16.5 lbs., Base Spread 30-1/2", Bottom Width 21-1/2"	
3AZX4	5 FT	Werner 7405	Ladder Height 5', Approx. Shipping Weight 20.0 lbs., Base Spread 36-3/4", Bottom Width 23-1/4"	AA
1XN72	6 FT	Werner 7406	Ladder Height 6', Approx. Shipping Weight 23.5 lbs., Base Spread 42-7/8", Bottom Width 25"'	
BAZX5	7 FT	Werner 7407	Ladder Height 7', Approx. Shipping Weight 28.0 lbs., Base Spread 49", Bottom Width 26-3/4"	
1XN73	8 FT	Werner 7408	Ladder Height 8', Approx. Shipping Weight 32.0 lbs., Base Spread 55-1/4", Bottom Width 28-1/2"	
IXN74	10 FT	Werner 7410	Ladder Height 10', Approx. Shipping Weight 40.5 lbs., Base Spread 67-1/2", Bottom Width 32"	
XN75	12 FT	Werner 7412	Ladder Height 12', Approx. Shipping Weight 49.5 lbs., Base Spread 79-7/8", Bottom Width 35-1/2"	
	_	si IAA city: 375 lbs	7300 SERIES STEPLADDER Patented EDGE® bracing provides enhanced bottom bracing protection against damage. Molded non-conductive extern bottom from damage. Large heavy duty aluminum knee bracar horizontals. Heavy-duty aluminum Tool-Tra-Top® seculotternal spreader bars.	al rail shields helps protect aces on all front steps and all
6JJ81	4 FT	Werner 7304	Ladder Height 4', Approx. Shipping Weight 16.0 lbs., Base Spread 29-3/4", Bottom Width 21-1/2"	An
BAZX3	5 FT	Werner 7305	Ladder Height 5', Approx. Shipping Weight 19.5 lbs., Base Spread 35-7/8", Bottom Width 23-1/4"	AA
6JJ82	6 FT	Werner 7306	Ladder Height 6', Approx. Shipping Weight 22.5 lbs., Base Spread 42", Bottom Width 25"'	AA
6JJ83	8 FT	Werner 7308	Ladder Height 8', Approx. Shipping Weight 31.0 lbs., Base Spread 54-3/4", Bottom Width 28-1/2"	
6JJ84	10 FT	Werner 7310	Ladder Height 10', Approx. Shipping Weight 40.5 lbs., Base Spread 66-5/8", Bottom Width 32"	
3JJ85	12 FT	Werner 7312	Ladder Height 12', Approx. Shipping Weight 49.5 lbs., Base Spread 79", Bottom Width 35-1/2"	V
		il IAA city: 375 lbs	6300 SERIES STEPLADDER Patented EDGE360™ feet provide protection from every an EDGE Bracing and Over-Sized feet and foot pads. Feature accommodate Lock-In accessories such as the ToolLasso slip-resistant Traction-Tred® steps. All steps and are kneehorizontals. Internal Spreader Bars.	rich LOCKTOP™ with slots to and JobBucket. Double riveted,
29JV18	4 FT	Werner 6304	Ladder Height 4', Approx. Shipping Weight 16.0 lbs., Base Spread 29", Bottom Width 19 7/8"	M
29JV20	5 FT	Werner 6305	Ladder Height 5', Approx. Shipping Weight 19.0 lbs., Base Spread 35-1/8", Bottom Width 21 5/8"	H
9JV21	6 FT	Werner 6306	Ladder Height 6', Approx. Shipping Weight 22.0 lbs., Base Spread 41-1/4", Bottom Width 23 3/8"	AS
29JV23	8 FT	Werner 6308	Ladder Height 8', Approx. Shipping Weight 31.0 lbs., Base Spread 53-5/8", Bottom Width 27 7/8"	HO
29JV25	10 FT	Werner 6310	Ladder Height 10', Approx. Shipping Weight 39.0 lbs., Base Spread 65-7/8", Bottom Width 30 3/8"	
29JV27	12 FT	Werner 6312	Ladder Height 12', Approx. Shipping Weight 48.0 lbs.,	V *

1



Grainger | Height | Model # | Description

FIBERGLASS STEPLADDERS continued

ANSI IA Load Capacity: 300 lbs		-	6200 SERIES STEPLADDER Patented EDGE360™ feet provide protection from every angle with integrated rail shield, EDGE Bracing and Over-Sized feet and foot pads. Feature rich LOCKTOP™ with slots to accommodate Lock-In accessories such as he ToolLasso and JobBucket. Double riveted, slip-resistant Traction-Tred® steps. All steps and are knee-braced. Full set of rear horizontal Internal Spreader Bars.		
41D245	3 FT	Werner 6203	Ladder Height 3', Approx. Shipping Weight 13.0#, Base Spread 23-1/8", Bottom Width 18-1/8"		
3W421	4 FT	Werner 6204	Ladder Height 4', Approx. Shipping Weight 16.0 lbs., Base Spread 29", Bottom Width 19-7/8"		
BAZX1	5 FT	Werner 6205	Ladder Height 5', Approx. Shipping Weight 19.0 lbs., Base Spread 35-1/8", Bottom Width 21-5/8"	RT.	
BW141	6 FT	Werner 6206	Ladder Height 6', Approx. Shipping Weight 22.0 lbs., Base Spread 41-1/4", Bottom Width 23-3/8"'		
BAZX2	7 FT	Werner 6207	Ladder Height 7', Approx. Shipping Weight 26.0 lbs., Base Spread 47-1/2", Bottom Width 25-1/8"	A9	
3W142	8 FT	Werner 6208	Ladder Height 8', Approx. Shipping Weight 30.0 lbs., Base Spread 53-5/8", Bottom Width 26-7/8"		
3W183	10 FT	Werner 6210	Ladder Height 10', Approx. Shipping Weight 39.0 lbs., Base Spread 65-7/8", Bottom Width 30-3/8"		
3W422	12 FT	Werner 6212	Ladder Height 12', Approx. Shipping Weight 48.0 lbs., Base Spread 78-1/4", Bottom Width 33-7/8"	Y	
		SI IA city: 300 lbs	6100 SERIES STEPLADDER Patented, molded, versatile HolsterTop® securely holds drills with sockets in back to accommodate Lock-In accessories JobBucket. Double riveted, slip-resistant Traction-Tred® ste Oversized, molded PROGUARD BOOTS™ provide firm slip-r fiberglass rail. Internal spreader bars.	such as he ToolLasso and ps. Full set of rear horizontals.	
29JV19	4 FT	Werner 6104	Ladder Height 4', Approx. Shipping Weight 15.0 lbs., Base Spread 28-7/8", Bottom Width 19"	M	
29JV22	6 FT	Werner 6106	Ladder Height 6', Approx. Shipping Weight 21.0 lbs., Base Spread 41-1/8", Bottom Width 22"	AQ	
29JV24	8 FT	Werner 6108	Ladder Height 8', Approx. Shipping Weight 30.0 lbs., Base Spread 53-1/2", Bottom Width 25"		
29JV26	10 FT	Werner 6110	Ladder Height 10', Approx. Shipping Weight 35.5 lbs., Base Spread 65-3/4", Bottom Width 28"		
29JV28	12 FT	Werner 6112	Ladder Height 12', Approx. Shipping Weight 44.0 lbs., Base Spread 78-1/8", Bottom Width 31"		
ANSI I Load Capacity: 250 lbs			6000 SERIES STEPLADDER Patented EDGE® bracing provides enhanced bottom bracing protection against damage. Patented, molded, versatile Hols other tools. Top is designed with sockets in back to accomm as the ToolLasso® and JobBucket. External spreader bars.	sterTop® securely holds drills a	
IW077	4 FT	Werner 6004	Ladder Height 4', Approx. Shipping Weight 13.0 lbs., Base Spread 28-7/8", Bottom Width 19"	ΛĀ	
AZW9	5 FT	Werner 6005	Ladder Height 5', Approx. Shipping Weight 16.0 lbs., Base Spread 35", Bottom Width 20-1/2"	JA	
	6 FT		Ladder Height 6', Approx. Shipping Weight 18.0 lbs.,		
W078	0	Werner 6006	Base Spread 41-1/8", Bottom Width 22"		



Grainger Item # Height Model # Description

LEANSAFE STEPLADDERS

LLAN	JAI L J	IEPLADDEI	10		
		SI IA city: 300 lbs	L6200 SERIES LEANING LADDER Featuring the LEANSAFE™ ladder top that secures tools and designed to securely lean against flat wall surfaces, wall corr perform as a standard stepladder. With a two color design and logos to make this ladder easily distinguishable from a stand ladder is the EDGE360 bracing to protect the bottom of the la	ers, poles and wall studs and d highly visible LEANSAFE™ ard stepladder. Anchoring the	
416K76	4 FT	L6204	Ladder Height 4', Reach Height is 8'. Base Spread 25", Approx. Ship Weight 16 lbs	A. O.	
416K77	6 FT	L6206	Ladder Height 6', Reach Height is 10'. Base Spread 38", Approx. Ship Weight 21 lbs		
416K78	8 FT	L6208	Ladder Height 8', Reach Height is 12'. Base Spread 50.25", Approx. Ship Weight 16 lbs		
416K79	10 FT	L6210	Ladder Height 10', Reach Height is 14'. Base Spread 62.5", Approx. Ship Weight 38 lbs	AH	
416K80	12 FT	L6212	Ladder Height 12', Reach Height is 16'. Base Spread 75", Approx. Ship Weight 49 lbs	7.1	
	_	il IAA city: 375 lbs	L7300 SERIES LEANING LADDER The LEANSAFE™ ladder top secures tools and accessories, securely lean against flat wall surfaces, wall corners, poles, a standard stepladder. Lower rear rail connection point allows when in stepladder mode. Single latch design stays engaged located to easily open and close. Ladder front feet have curve that maximize the surface area in both the stepladder and lea	nd wall studs or performs as a user to get closer to the work when needed, and is centrally ed non-marring rubber foot pads	
458R92	4 FT	Werner L7304	Ladder Height 4', Reach height 8'. Approx. Ship Weight 16 lbs., Base Spread 25", Bottom Width 20.5"	9 =3	
458R93	6 FT	Werner L7306	Ladder Height 6', Reach height 10'. Approx. Ship Weight 21 lbs., Base Spread 38", Bottom Width 24"		
458R94	8 FT	Werner L7308	Ladder Height 8', Reach height 12'. Approx. Ship Weight 29 lbs., Base Spread 50", Bottom Width 27.5"		
458R95	10 FT	Werner L7310	Ladder Height 10', Reach height 14'. Approx. Ship Weight 38 lbs., Base Spread 62.5", Bottom Width 31"		
458R96	12 FT	Werner L7312	Ladder Height 12', Reach height 16'. Approx. Ship Weight 49 lbs., Base Spread 75", Bottom Width 35"		



DUAL PURPOSE LADDERS

DUAL	PURP	OSE LADDE	:RS	
	ANSI IA Load Capacity: 300 lbs		DP6200 SERIES DUAL PURPOSE 2-IN-1 LADDER The DP6206 6 ft Fiberglass Dual Purpose Ladder features a 2-in-1 design that can act as both as stepladder and an extension ladder. With a simple Flip and Click the ladder easily converts from one position to the other. The full 3 inch steps run up the entire ladder offering better standing comfort than a traditional extension ladder at any height. The DP6206 features a padded V-Rung for working on corners, pole, and trees. The oversized, molded PROGUARD BOOTS™ provide the firm slip-resistant footing and protect the fiberglass rail.	
53KC25	6 FT	DP6206	Closed Height 73-1/16", Reach Height Extension Ladder 13', Highest Standing Level-Extension ladder 6'-8". Reach Height Stepladder 10', Stepladder Height 6', Approx. Ship Weight 28 lbs	A
53KC26	7 FT	DP6207	Closed Height 85-1/16", Reach Height Extension Ladder 15', Highest Standing Level-Extension ladder 8'-7". Reach Height Stepladder 11', Stepladder Height 7', Approx. Ship Weight 33 lbs	A A
53KC27	8 FT	DP6208	Closed Height 97-1/16", Reach Height Extension Ladder 17', Highest Standing Level-Extension ladder 10'-7". Reach Height Stepladder 12', Stepladder Height 8', Approx. Ship Weight 38 lbs	



Grainger Item # Height Model # Description

FIBERGLASS PODIUM LADDERS

	ANSI IAA Load Capacity: 375 lbs		PD7300 SERIES PODIUM LADDER Ideal for working at fixed heights. Extra large platform for long standing comfort and allows you to work safely in any direction. Waist high guard rail wraps around work zone and securely holds tools. Slip-resistant steps are knee-braced and double riveted. The EDGE360® bracing system gives protection from every angle and oversized foot pads.	
36FX50	6 FT	Werner PD7303	Ladder Height 6', Platform Height is 3'. Approx. Ship Weight 22.5 lbs., Base Spread 36", Bottom Width 26 "	17
36FX51	7 FT	Werner PD7304	Ladder Height 7', Platform Height is 4'. Approx. Ship Weight 28.0 lbs., Base Spread 42", Bottom Width 27 "	//\
36FX52	9 FT	Werner PD7306	Ladder Height 9', Platform Height is 6'. Approx. Ship Weight 34 lbs., Base Spread 55", Bottom Width 31"	A
36FX53	11 FT	Werner PD7308	Ladder Height 11', Platform Height is 8'. Approx. Ship Weight 46 lbs., Base Spread 69", Bottom Width 35 "	AH
458R97	13 FT	3 FT Werner PD7310	Ladder Height 13', Platform Height is 10'. Approx. Ship Weight 65 lbs., Base Spread 79", Bottom Width 38"	, ,,
		SI IA	PD6200 SERIES PODIUM LADDER Ideal for working at fixed heights. Extra large platform for long	standing comfort and allows
	Loau Capa	icity: 300 lbs	you to work safely in any direction. Waist high guard rail wraps securely holds tools. Slip-resistant steps are knee-braced and bracing system gives protection from every angle. Oversized f	s around work zone and double riveted. The EDGE360
20KJ26	6 FT	Werner PD6203	securely holds tools. Slip-resistant steps are knee-braced and	s around work zone and double riveted. The EDGE360
20KJ26 20KJ27	•		securely holds tools. Slip-resistant steps are knee-braced and bracing system gives protection from every angle. Oversized for Ladder Height 6', Platform Height is 3'. Approx. Ship	s around work zone and double riveted. The EDGE360
	6 FT	Werner PD6203	securely holds tools. Slip-resistant steps are knee-braced and bracing system gives protection from every angle. Oversized for Ladder Height 6', Platform Height is 3'. Approx. Ship Weight 22.5#, Base Spread 36", Bottom Width 26" Ladder Height 7', Platform Height is 4'. Approx. Ship	s around work zone and double riveted. The EDGE360
20KJ27	6 FT 7 FT	Werner PD6203 Werner PD6204	securely holds tools. Slip-resistant steps are knee-braced and bracing system gives protection from every angle. Oversized for Ladder Height 6', Platform Height is 3'. Approx. Ship Weight 22.5#, Base Spread 36", Bottom Width 26" Ladder Height 7', Platform Height is 4'. Approx. Ship Weight 28.0#, Base Spread 42", Bottom Width 27" Ladder Height 9', Platform Height is 6'. Approx. Ship	s around work zone and double riveted. The EDGE360



FIBERGLASS PODIUM LADDERS WITH CASTERS

ANSI IAA Load Capacity: 375 lbs			PD7300-4C SERIES PODIUM LADDER WITH CASTERS Ideal for working at fixed heights. Extra large platform for you to work safely in any direcition. Waist high guard rail securely holds tools. Slip-resistant steps are knee-braced assemblies with stainless steel springs & heavy duty step	wraps around work zone and I and double riveted. Durable caster
45ED69	6 FT	Werner PD7303-4C	Ladder Height 6', Platform Height is 3'. Approx. Ship Weight 22.5 lbs., Base Spread 36", Bottom Width 26 "	**
45ED70	7 FT	Werner PD7304-4C	Ladder Height 7', Platform Height is 4'. Approx. Ship Weight 28.0 lbs., Base Spread 42", Bottom Width 27 "	\mathcal{M}
45ED71	9 FT	Werner PD7306-4C	Ladder Height 9', Platform Height is 6'. Approx. Ship Weight 34 lbs., Base Spread 55", Bottom Width 31"	
45ED72	11 FT	Werner PD7308-4C	Ladder Height 11', Platform Height is 8'. Approx. Ship Weight 46 lbs., Base Spread 69", Bottom Width 35 "	A
458R98	13 FT	Werner PD7310-4C	Ladder Height 13', Platform Height is 10'. Approx. Ship Weight 65 lbs., Base Spread 79", Bottom Width 38"	\$ 5



Grainger Item # Height Model # Description

FIBERGLASS PODIUM LADDERS WITH CASTERS

ANSI IA Load Capacity: 300 lbs			PD6200-4C SERIES PODIUM LADDER WITH CASTERS Ideal for working at fixed heights. Extra large platform for log you to work safely in any direction. Waist high guard rail we securely holds tools. Slip-resistant steps are knee-braced a assemlies with stainless steel springs & heavy duty step by	raps around work zone and and and double riveted. Durable caster
45ED64	6 FT	Werner PD6203-4C	Ladder Height 6', Platform Height is 3'. Approx. Ship Weight 22.5 lbs., Base Spread 36", Bottom Width 26 "	
45ED65	7 FT	Werner PD6204-4C	Ladder Height 7', Platform Height is 4'. Approx. Ship Weight 28.0 lbs., Base Spread 42", Bottom Width 27 "	$\Lambda\Lambda$
45ED66	9 FT	Werner PD6206-4C	Ladder Height 9', Platform Height is 6'. Approx. Ship Weight 34 lbs., Base Spread 55", Bottom Width 31"	
45ED67	11 FT	Werner PD6208-4C	Ladder Height 11', Platform Height is 8'. Approx. Ship Weight 46 lbs., Base Spread 69", Bottom Width 35 "	
45ED68	13 FT	Werner PD6210-4C	Ladder Height 13', Platform Height is 10'. Approx. Ship Weight 57 lbs., Base Spread 79", Bottom Width 38 "	N. o.

FIRERGIASS DI ATFORM I ADDERS

FIBER	IGLASS	PLATFORM	1 LADDERS
Lo		AA / IA /: 375 / 300 lbs	P7400 SERIES PLATFORM STEPLADDER Safety guard rail encourages proper ladder use. Large platform provides secure and comfortable work area. Slip-resistant Traction-Tred® extra wide steps are knee-braced aldouble riveted. The EDGE® bracing system helps to decrease damage to rail. Aluminum external rail shields provide additional reinforcement to the bottom.
6W679	6 FT 375 lbs	Werner P7404	Ladder Height 6', Platform Height 4'. Approx. Shipping Weight 26.0 lbs., Base Spread 42", Bottom Width 27"
3W186	8 FT 375 lbs	Werner P7406	Ladder Height 8', Platform Height 6'. Approx. Shipping Weight 34.0 lbs., Base Spread 54-3/8", Bottom Width 30-1/2"
6W680	10 FT 375 lbs	Werner P7408	Ladder Height 10', Platform Height 8'. Approx. Shipping Weight 44.5 lbs., Base Spread 66-5/8", Bottom Width 34"
4XP29	12 FT 300 lbs	Werner P7410	Ladder Height 12', Platform Height 10'. Approx. Shipping Weight 54.5 lbs., Base Spread 79", Bottom Width 37-1/2 "
		SI IA city: 300 lbs	P6200 SERIES STEPLADDER Safety guard rail encourages proper ladder use. Large platform provides secure and comfortable work area. Slip-resistant Traction-Tred® steps are double riveted. Patented EDGE360™ feet provide protection from every angle with integrated rail shield, EDGE Bracing and over-sized feet and foot pads.
4EB96	6 FT	Werner P6204	Ladder Height 6', Platform Height 4', Approx. Shipping Weight 24.0 lbs., Base Spread 42", Bottom Width 26-7/8 "
4EB97	8 FT	Werner P6206	Ladder Height 8', Platform Height 6', Approx. Shipping Weight 32.0 lbs., Base Spread 54-3/4", Bottom Width 30-3/8"
4EB98	10 FT	Werner P6208	Ladder Height 10', Platform Height 8', Approx. Shipping Weight 44.5 lbs., Base Spread 66-5/8", Bottom Width 33-78"
3AZY5	12 FT	Werner P6210	Ladder Height 12', Platform Height 10', Approx. Shipping Weight 55.0 lbs., Base Spread 79", Bottom Width 37-3/8"





Grainger Height Model # Description Item #

FIBERGLASS STOCKR'S® LADDERS

ANSI IA Load Capacity: 300 lbs (per side)		~	PT7400-4C SERIES STOCKR'S LADDER® Safety guard rail. Large platform. Slip-resistant Traction-Tractions. Soft rubber wheels are easy on vinyl floors and daspring-loaded casters allow easy 360° mobility.	•
3AZY6	6 FT	Werner PT7404-4C	Ladder Height 6', Platform Height 4', Approx. Shipping Weight 37.0 lbs., Base Spread 50", Bottom Width 25-1/4"	a of T
4XP39	8 FT	Werner PT7406-4C	Ladder Height 8', Platform Height 6', Approx. Shipping Weight 53.0 lbs., Base Spread 64", Bottom Width 28-3/4"	
4XP40	10 FT	Werner PT7408-4C	Ladder Height 10', Platform Height 8', Approx. Shipping Weight 60.5 lbs., Base Spread 78-1/4", Bottom Width 32-1/4"	AA
4XP41	12 FT	Werner PT7410-4C	Ladder Height 12', Platform Height 10', Approx. Shipping Weight 72.5 lbs., Base Spread 92-1/4", Bottom Width 35-3/4"	



FIBERGLASS TRIPOD LADDER

ANSI IA Load Capacity: 300 lbs		~	FTP6200 SERIES TRIPOD STEPLADDER Tripod ladders make it possible to work in tight areas, around corners, and through study 3-legged design stays stable on uneven surfaces. Molded, versatile top securely holds of and many other tools.	
4ZY19	4 FT	Werner FTP6204	Ladder Height 4', Approx. Shipping Weight 17.0 lbs., Base Spread 30-1/2", Bottom Width 31"	
4EB99	6 FT	Werner FTP6206	Ladder Height 6', Approx. Shipping Weight 23.0 lbs., Base Spread 43-3/4", Bottom Width 36"	
4ZY20	8 FT	Werner FTP6208	Ladder Height 8', Approx. Shipping Weight 31.0 lbs., Base Spread 57", Bottom Width 40"	
41D249	10 FT	Werner FTP6210	Ladder Height 10', Approx. Ship Wt. 42.0#, Base Spread 71", Bottom Width 51"	
41D250	12 FT	Werner FTP6212	Ladder Height 12', Approx. Ship Wt. 51.0#, Base Spread	

77-3/4", Bottom Width 54"



ELECTRICIAN'S JOBSTATION™

ANSI IAA Load Capacity: 375 lbs			OBEL00 SERIES ELECTRICIAN'S JOBSTATION™ Specifically designed for the electrical contractor with integr spool holders and multi-use hook. Custom designed Holster pipes up to 1" diameter and includes measuring scale and to in back to accommodate Lock-In Accessories such as the To	Top® is equipped with groove to hold ol slots. Top is designed with sockets
1FCF1	4 FT	Werner OBEL04	Ladder Height 4', Approx. Shipping Weight 16.0 lbs., Base Spread 29", Base Width 19-7/8" Note: Conduit holder not available on 4' model	7
1FCF2	6 FT	Werner OBEL06	Ladder Height 6', Approx. Shipping Weight 24.0 lbs., Base Spread 41-1/4", Bottom Width 23-3/8"	A
1FCF3	8 FT	Werner OBEL08	Ladder Height 8', Approx. Shipping Weight 32.0 lbs., Base Spread 53-5/8", Bottom Width 26-7/8"	
1FCF4	10 FT	Werner OBEL10	Ladder Height 10', Approx. Shipping Weight 41.0 lbs., Base Spread 65-7/8", Bottom Width 30-3/8"	
1FCF5	12 FT	Werner OBEL12	Ladder Height 12', Approx. Shipping Weight 51.5 lbs., Base Spread 78-1/4", Bottom Width 33-7/8"	



Grainger | Height | Model # | Description

FIBERGLASS EXTENSION/TRESTLE LADDER

Load		SI IA 300 lbs (per side)	E7400 SERIES EXTENSION/TRESTLE LADDER Twin stepladders with extendable trestle section. Patented bottom bracing strength and increased protection against shields provide additional reinforcement to the bottom.	
4XP05	8 FT	Werner E7408	Stepladder Height 8', Extended Ladder Height 12', Base Section Width 32-3/4", Spread 67-3/4"	Ы
4XP06	10 ft.	Werner E7410	Stepladder Height 10', Extended Ladder Height 15', Base Section Width 36-1/4", Spread 81-7/8"	
4XP07	12 FT	Werner E7412	Stepladder Height 12', Extended Ladder Height 19', Base Section Width 39-3/4", Spread 95-7/8"	
4XP08	14 FT	Werner E7414	Stepladder Height 14', Extended Ladder Height 22', Base Section Width 43-1/4", Spread 109-3/4"	
4XP09	16 FT	Werner E7416	Stepladder Height 16', Extended Ladder Height 26', Base Section Width 46-3/4", Spread 123-3/4"	
CIDED	CI ACC	TWIN STEE	OI ADDEDS	

4XP09	10 F I	werner E/416	Base Section Width 46-3/4", Spread 123-3/4"	
FIBER	GLASS	TWIN STEP	LADDERS	
Load Ca	_	AA / IA 5 / 300 lbs (per side)	T7400 SERIES TWIN STEPLADDER Twin Stepladders are great for two-person jobs. Patented ED bottom bracing strength and increased protection against de shields provide additional reinforcement to the bottom. Larg braces on all front and back steps. Heavy-duty aluminum To-	amage. Aluminum external rail e heavy duty aluminum knee
4XP48	4 FT 375 lbs	Werner T7404	Ladder Height 4', Approx. Shipping Weight 21.5 lbs., Base Spread 36-1/8", Bottom Width 21-1/2"	
41D242	5 FT 375 lbs	Werner T7405	Ladder Height 5', Approx. Shipping Weight 29.0#, Base Spread 43-1/8", Bottom Width 23-1/2"	Sh. Ti
4XP49	6 FT 375 lbs	Werner T7406	Ladder Height 6', Approx. Shipping Weight 30.0 lbs., Base Spread 50-1/8", Bottom Width 25"	A.A.
4XP50	8 FT 375 lbs	Werner T7408	Ladder Height 8', Approx. Shipping Weight 40.5 lbs., Base Spread 64-1/8", Bottom Width 28-1/2"	
4XP51	10 FT 375 lbs	Werner T7410	Ladder Height 10', Approx. Shipping Weight 51.5 lbs., Base Spread 78-1/4", Bottom Width 32"	
4XP52	12 FT 375 lbs	Werner T7412	Ladder Height 12', Approx. Shipping Weight 63.5 lbs., Base Spread 92-1/4", Bottom Width 35-1/2"	
4XP53	14 FT 300 lbs	Werner T7414	Ladder Height 14', Approx. Shipping Weight 86.0 lbs., Base Spread 106-1/4", Bottom Width 39"	
4XP54	16 FT 300 lbs	Werner T7416	Ladder Height 16', Approx. Shipping Weight 103.5 lbs., Base Spread 120-1/4", Bottom Width 42-1/8"	4
4XP55	20 FT 300 lbs	Werner T7420	Ladder Height 20', Approx. Shipping Weight 149.0 lbs., Base Spread 150-1/8", Bottom Width 49-1/2"	
Load		SI IA 300 lbs (per side)	T6200 SERIES STEPLADDER Twin Stepladders are great for two-person jobs. Patented in securely holds drills and other tools. Slip-resistant Traction Patented EDGE360™ feet provide protection from every ar EDGE Bracing and over-sized feet and foot pads.	n-Tred [®] steps are double riveted.
6YG79	4 FT	Werner T6204	Ladder Height 4', Approx. Shipping Weight 19.0 lbs., Base Spread 36-1/8", Bottom Width 19-7/8"	
3AZX6	5 FT	Werner T6205	Ladder Height 5', Approx. Shipping Weight 23.0 lbs., Base Spread 43-1/8", Bottom Width 21-5/8"	

Ladder Height 6', Approx. Shipping Weight 27.0 lbs.,

Ladder Height 8', Approx. Shipping Weight 37.0 lbs.,

Ladder Height 10', Approx. Shipping Weight 54.5 lbs.,

Ladder Height 12', Approx. Shipping Weight 68.5 lbs.,

Base Spread 50-1/8", Bottom Width 23-3/8"

Base Spread 64-1/8", Bottom Width 26-7/8"

Base Spread 78-1/8", Bottom Width 30-3/8"

Base Spread 92-1/8", Bottom Width 33-7/8"



6 FT

8 FT

10 FT

12 FT

Werner T6206

Werner T6208

Werner T6210

Werner T6212

6YG80

6YG81

3AZX7

3AZX8



Grainger | Height | Model # | Description

ALUMINUM STEPLADDERS

L	ANSI IAA Load Capacity: :		400 SERIES STEPLADDER Aluminum stepladder features heavy gauge aluminum Tool-Tra-Top®. All steps are kne braced. Slip-resistant Traction-Tred® steps. Full set of rear horizontals. Slip-resistant foot pads.	
4XN58	4 FT 375 lbs	Werner 404	Ladder Height 4', Approx. Shipping Weight 16.0 lbs., Base Spread 30-1/8", Bottom Width 21-1/4"	
4XN59	6 FT 375 lbs	Werner 406	Ladder Height 6', Approx. Shipping Weight 24.0 lbs., Base Spread 42-7/16", Bottom Width 24-3/4"	
4XN60	8 FT 375 lbs	Werner 408	Ladder Height 8', Approx. Shipping Weight 33.5 lbs., Base Spread 54-3/4", Bottom Width 28-1/4"	
4XN61	10 FT 375 lbs	Werner 410	Ladder Height 10', Approx. Shipping Weight 43.5 lbs., Base Spread 67", Bottom Width 31-1/4"	
4XN63	12 FT 375 lbs	Werner 412	Ladder Height 12', Approx. Shipping Weight 54.5 lbs., Base Spread 79-3/8", Bottom Width 35-1/4"	
4XN64	14 FT 300 lbs	Werner 414	Ladder Height 14', Approx. Shipping Weight 65.0 lbs., Base Spread 91-11/16", Bottom Width 38-5/8"	
4XN67	16 FT 300 lbs	Werner 416	Ladder Height 16', Approx. Shipping Weight 77.5 lbs., Base Spread 104", Bottom Width 42-1/8"	
	ANSI Load Capacit		370 SERIES STEPLADDER Aluminum stepladder features Tool-Tra-Top®. Sturdy Spill-Proof® pail shelf. Double rive slip-resistant Traction-Tred® steps. Full set of rear horizontals. Unique "H" spreader wi grip on 4', 5' and 6' for easy one-handed carry and close.	
2EJG8	3 FT	Werner 373	Ladder Height 3', Approx. Shipping Weight 9.0 lbs., Base Spread 23-3/8", Bottom Width 17-3/4"	
4W074	4 FT	Werner 374	Ladder Height 4', Approx. Shipping Weight 11.0 lbs., Base Spread 29-1/2", Bottom Width 19-1/2"	
3AZX9	5 FT	Werner 375	Ladder Height 5', Approx. Shipping Weight 13.5 lbs., Base Spread 35-3/4", Bottom Width 21-1/4"	
3W423	6 FT	Werner 376	Ladder Height 6', Approx. Shipping Weight 15.5 lbs., Base Spread 41-7/8", Bottom Width 23"	
3W424	8 FT	Werner 378	Ladder Height 8', Approx. Shipping Weight 22.5 lbs., Base Spread 54-1/4", Bottom Width 26-1/2"	
4W172	10 FT	Werner 310	Ladder Height 10', Approx. Shipping Weight 31.0 lbs., Base Spread 66-1/2", Bottom Width 30"	
	ANSI Load Capacit		360 SERIES STEPLADDER Aluminum stepladder features Tool-Tra-Top® with convenient tray for tools, paint can a slots for paint roller tray and paint can hanger on back. Automatic Spill-Proof® pail should that opens and closes with ladder and has slots to hold tools, rag bar and paint can. Step resistant molded feet. External spreader bars.	elf
41D304	4 FT	Werner 364	Ladder Height 4' Approx. Ship Weight 10.5 lbs., Base Spread 29 1/4", Bottom Width 18 1/2"	
41D305	5 FT	Werner 365	Ladder Height 5' Approx. Ship Weight 12.5 lbs., Base Spread 35 1/2", Bottom Width 20"	
41D306	6 FT	Werner 366	Ladder Height 6' Approx. Ship Weight 14.5 lbs., Base Spread 41 5/8", Bottom Width 21 1/2 "	
4GNK8	8 FT	Werner 368	Ladder Height 8' Approx. Ship Weight 21.5 lbs., Base Spread 54", Bottom Width 24 1/2 "	



Grainger Height Model # Description Item #

ALUMINUM PLATFORM LADDERS

ANSI IAA Load Capacity: 375 lbs			P400 SERIES PLATFORM STEPLADDER Large platform provides secure and comfortable work area 225 square inches of platform standing area. Heavy duty kn Shoulder bolt with locknut on top hinge.	
6W686	6 FT	Werner P404	Ladder Height 6', Platform Height 4', Approx. Shipping Weight 25.0 lbs., Base Spread 42-1/16", Bottom Width 24-3/4"	
6W687	8 FT	Werner P406	Ladder Height 8', Platform Height 6', Approx. Shipping Weight 33.5 lbs., Base Spread 54-3/4", Bottom Width 28-1/4"	A
6W688	10 FT	Werner P408	Ladder Height 10', Platform Height 8', Approx. Shipping Weight 45.5 lbs., Base Spread 79-1/2", Bottom Width 31-3/4"	



ALUMINUM TWIN STEPLADDERS

ANSI IA Load Capacity: 300 lbs (per side)			T370 SERIES TWIN STEPLADDER Twin Stepladders are great for two-person jobs. Double rive steps. Full set of rear horizontals. Internal spreader bars.	eted slip-resistant Traction-Tred®
3AZY1	4 FT	Werner T374	Ladder Height 4', Approx. Shipping Weight 14.5 lbs., Base Spread 36", Bottom Width 21-1/4"	AL
3AZY2	6 FT	Werner T376	Ladder Height 6', Approx. Shipping Weight 21.5 lbs., Base Spread 50", Bottom Width 24-3/4"	
3AZY3	8 FT	Werner T378	Ladder Height 8', Approx. Shipping Weight 31.0 lbs., Base Spread 64", Bottom Width 28-1/4"	AB
3AZY4	10 FT	Werner T310	Ladder Height 10', Approx. Shipping Weight 43.0 lbs., Base Spread 78", Bottom Width 31-3/4"	



ALUMINUM TELESCOPING MULTIPURPOSE LADDERS

ANSI IA Load Capacity: 300 lbs			MT SERIES TELESCOPING MULTILADDER Easily converts into 4 positions - Twin Stepladder, Stairway Ladder, 2-Scaffold Bases. Smooth curved rails for comfortable climbing. Do long lasting durability. Extra wide flared bottom for firm support. Sli	uble riveted steps for
2NKW6	13 FT	Werner MT-13	Stepladder Height = 3' to 5' • Extension Ladder Height = 7' to 11' Stairway Ladder Height = 3' to 5' • Scaffold Position Length = 1' to 2' Weight = 31.6 lbs.	
2NKW7	17 FT	Werner MT-17	Stepladder Height = 4' to 7' • Extension Ladder Height = 9' to 15' Stairway Ladder Height = 4' to 7' • Scaffold Position Length = 1' to 3' Weight = 39.6 lbs.	Ä
2NKW8	22 FT	Werner MT-22	Stepladder Height = 5' to 9' • Extension Ladder Height = 11' to 19' Stairway Ladder Height = 5' to 9' • Scaffold Position Length = 1' to 4' Weight = 47.0 lbs.	AA
2NKW9	26 FT	Werner MT-26	Stepladder Height = 6' to 11' • Extension Ladder Height = 13' to 23' Stairway Ladder Height = 6' to 11' • Scaffold Position Length = 1' to 5' Weight = 62.6 lbs.	AHH



Grainger | Height | Model # | Description

FIBERGLASS EXTENSION LADDERS

Load C	ANSI I Capacity: (375	AA / IA 5 / 300 lbs as noted)	D7100-2 SERIES EXTENSION LADDER ALFLO® rung joints for Twist-Proof® performance. Rung replacement. Slip-resistant Traction-Tred® D-rungs. Com rubber pads for hard surfaces or swivel the shoe to use surfaces. Note: 16' No. 4XN97 is not equipped with rope	hbination shoes with slip-resistant the spur plates for penetrable
4XN97	16 FT 375 lbs	Werner D7116-2	Ladder Height 16', Maximum Working Length 13', Approx. Shipping Weight 41.0 lbs.	4
4XN98	20 FT 375 lbs	Werner D7120-2	Ladder Height 20', Maximum Working Length 17', Approx. Shipping Weight 50.0 lbs.	
4XN99	24 FT 375 lbs	Werner D7124-2	Ladder Height 24', Maximum Working Length 21', Approx. Shipping Weight 58.5 lbs.	Dung plate
4XP01	28 FT 375 lbs	Werner D7128-2	Ladder Height 28', Maximum Working Length 25', Approx. Shipping Weight 67.0 lbs.	Rung-plate connection
4XP02	32 FT 375 lbs	Werner D7132-2	Ladder Height 32', Maximum Working Length 29', Approx. Shipping Weight 82.5 lbs.	H
3W621	40 FT 300 lbs	Werner D7140-2	Ladder Height 40', Maximum Working Length 35', Approx. Shipping Weight 126.5 lbs.	H
	ANS Load Capad		D6200-2 SERIES EXTENSION LADDER ALFLO® rung joints for Twist-Proof® performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for performance.	slip-resistant rubber pads for hard enetrable surfaces.
3W620			ALFLO® rung joints for Twist-Proof® performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for pe	slip-resistant rubber pads for hard enetrable surfaces.
3W620 3W184	Load Capac	sity: 300 lbs	ALFLO® rung joints for Twist-Proof® performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for pe Note: 16' Item 3W620 is not equipped with rope and pulled Ladder Height 16', Maximum Working Length13',	slip-resistant rubber pads for hard enetrable surfaces.
	Load Capac	Werner D6216-2	ALFLO® rung joints for Twist-Proof® performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for pe Note: 16' Item 3W620 is not equipped with rope and pulled Ladder Height 16', Maximum Working Length13', Approx. Shipping Weight 36.5 lbs. Ladder Height 20', Maximum Working Length 17',	slip-resistant rubber pads for hard enetrable surfaces.
3W184	16 FT 20 FT	Werner D6216-2 Werner D6220-2	ALFLO® rung joints for Twist-Proof® performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for pe Note: 16' Item 3W620 is not equipped with rope and pulled Ladder Height 16', Maximum Working Length 13', Approx. Shipping Weight 36.5 lbs. Ladder Height 20', Maximum Working Length 17', Approx. Shipping Weight 44.5 lbs. Ladder Height 24', Maximum Working Length 21',	slip-resistant rubber pads for hard enetrable surfaces. ey.
3W184 3W139	16 FT 20 FT 24 FT	Werner D6216-2 Werner D6220-2 Werner D6224-2	ALFLO® rung joints for Twist-Proof® performance. Direct resistant Traction-Tred® rungs. Combination shoes with surfaces or swivel the shoe to use the spur plates for pe Note: 16' Item 3W620 is not equipped with rope and pulled Ladder Height 16', Maximum Working Length 13', Approx. Shipping Weight 36.5 lbs. Ladder Height 20', Maximum Working Length 17', Approx. Shipping Weight 44.5 lbs. Ladder Height 24', Maximum Working Length 21', Approx. Shipping Weight 52.0 lbs. Ladder Height 28', Maximum Working Length 25',	slip-resistant rubber pads for hard enetrable surfaces. ey. ALFLO® Rung-to_Rail

FIBERGLASS COMBINATION LADDERS

		SI IAA acity: 375 lbs	7800 SERIES FIBERGLASS COMBINATION STEP/EXTENSION LAD Fiberglass combination ladders provide dual functionality in one I a stepladder to extension ladder and back. ALFLO® rung joint conf	adder. Easily converts from
4XN76	6 FT	Werner 7806	Stepladder Height 6', Extended ladder working length 9-1/2', Base Width 23-1/4' at flared base, Stepladder spread to outside of shoes 46-1/2", Approx. Shipping Weight 33.5 lbs.	Ħ
6W679	7 FT	Werner 7807	Stepladder Height 7', Extended ladder working length 11-1/2'. Base Width 24-1/4" at flared base, Stepladder spread to outside of shoes 53-1/2", Approx. Shipping Weight 37.0 lbs.	HA
4XN77	8 FT	Werner 7808	Stepladder Height 8', Extended ladder working length 13-1/2'., Base Width 25-1/4" at flared base, Stepladder spread to outside of shoes 60-1/2", Approx. Shipping Weight 40.5 lbs.	AH



Grainger | Height | Model # | Description

ALUMINUM EXTENSION LADDERS

aluminum gravity spring locks. Note: 16' Item 4XN89 is not equipped with rope and pulley.	se with ruded
4XN89 16 FT Werner D1516-2 Ladder Height 16', Maximum Working Length 13', Approx. Shipping Weight 30.5 lbs.	
4XN90 20 FT Werner D1520-2 Ladder Height 20', Maximum Working Length 17', Approx. Shipping Weight 37.0 lbs.	
4XN91 24 FT Werner D1524-2 Ladder Height 24', Maximum Working Length 21', Approx. Shipping Weight 45.0 lbs.	
4XN92 28 FT Werner D1528-2 Ladder Height 28', Maximum Working Length 25', Approx. Shipping Weight 56.0 lbs.	
4XN93 32 FT Werner D1532-2 Ladder Height 32', Maximum Working Length 29', Approx. Shipping Weight 67.0 lbs.	
4XN94 36 FT Werner D1536-2 Ladder Height 36', Maximum Working Length 32', Approx. Shipping Weight 80.0 lbs.	
4XN95 40 FT Werner D1540-2 Ladder Height 40', Maximum Working Length 35', Approx. Shipping Weight 89.5 lbs.	



ANSI IAA Load Capacity: 375 lbs.			D7200-2 SERIES EXTENSION LADDER Lightweight Fiberglass Extension Ladder provides same du ALFLO® rung joints for Twist-Proof® performance. Rung plat replacement. Slip-resistant Traction-Tred® D-Rungs. Combin rubber pads for hard surfaces or swivel the shoes to use sp	e connection for easy rung ation shoes with slip-resistant
36FX58	16 FT	Werner D7216-2	Ladder Height 16', Maximum Working Length 13', Approx. Ship Weight 36 lbs.	H
36FX59	20 FT	Werner D7220-2	Ladder Height 20', Maximum Working Length 17', Approx. Ship Weight 44 lbs.	<u>H</u>
36FX60	24 FT	Werner D7224-2	Ladder Height 24', Maximum Working Length 21', Approx. Ship Weight 51 lbs.	H
36FX61	FX61 28 FT Werner D7228-2		Ladder Height 28', Maximum Working Length 25',	A
			Approx. Ship Weight 58 lbs.	1 ·
		SI IA city: 300 lbs	D6400-2 SERIES EXTENSION LADDER Lightweight Fiberglass Extension Ladder provides same du ALFLO® rung joints for Twist-Proof® performance. Direct Rui Traction-Tred® D-Rungs. Combination shoes with slip-resist swivel the shoes to use spur plates for penetrable surfaces.	ng to Rail connections. Slip-resistant ant rubber pads for hard surfaces or
36FX54		~	D6400-2 SERIES EXTENSION LADDER Lightweight Fiberglass Extension Ladder provides same du ALFLO® rung joints for Twist-Proof® performance. Direct Ru Traction-Tred® D-Rungs. Combination shoes with slip-resist	ng to Rail connections. Slip-resistant ant rubber pads for hard surfaces or
36FX54 36FX55	Load Capa	city: 300 lbs	D6400-2 SERIES EXTENSION LADDER Lightweight Fiberglass Extension Ladder provides same du ALFLO® rung joints for Twist-Proof® performance. Direct Ru Traction-Tred® D-Rungs. Combination shoes with slip-resist swivel the shoes to use spur plates for penetrable surfaces. Ladder Height 16', Maximum Working Length 13',	ng to Rail connections. Slip-resistant ant rubber pads for hard surfaces or
	Load Capa	City: 300 lbs Werner D6416-2	D6400-2 SERIES EXTENSION LADDER Lightweight Fiberglass Extension Ladder provides same du ALFLO® rung joints for Twist-Proof® performance. Direct Rui Traction-Tred® D-Rungs. Combination shoes with slip-resist swivel the shoes to use spur plates for penetrable surfaces. Ladder Height 16', Maximum Working Length 13', Approx. Ship Weight 32 lbs. Ladder Height 20', Maximum Working Length 17',	ng to Rail connections. Slip-resistant ant rubber pads for hard surfaces or



Grainger Height Model # Description item #

FIBERGLASS EXTENSION LADDERS WITH LEVELERS

	ANSI IAA Load Capacity: 375 lbs.		D7100-2LV SERIES EXTENSION LADDER Fiberglass D-rung extension ladder with rung plate rung-to installed LeveLok® Levelers enable ladder to adapt to unevel Leveler extends up to 10" in 3/16" increments. Pre-pierced h installation of accessories. Base and fly separate easily to Ideal for utility and telecommunication industries.	en terrain with simple foot action, noles at top of ladder for easy field
3AZT2	20 FT	Werner D7120-2LV	Ladder Height 20', Approx. Shipping Weight 58.0 lbs. Maximum Working Length 17', Outside Shoe Base Width 22-3/4"	24
3AZT3	24 FT	Werner D7124-2LV	Ladder Height 24', Approx. Shipping Weight 66.5 lbs. Maximum Working Length 21', Outside Shoe Base Width 22-3/4"	
3AZT4	28 FT	Werner D7128-2LV	Ladder Height 28', Approx. Shipping Weight 75.0 lbs. Maximum Working Length 25', Outside Shoe Base Width 22-3/4"	



FIBERGLASS MULTI-POSITION LADDERS

ı		SI IA city: 300 lbs.	FMT SERIES TELESCOPING MULTILADDER Multi-Purpose Fiberglass 5-in-1 Ladder. Easily converts into 5 position Stairway Ladder, Extension Ladder, Wall Ladder, 2-Scaffold Bases. Nor rails. Impact resistant push knobs. Shater-Proof J-Locks. Double rivete bottom for firm support. Slip-resistant feet. Compact position for easy	n-conductive side ed steps. Wide flared
494M33	13 FT	Werner FMT-13	 Stepladder Height = 3' to 5' Extension Ladder Height = 7' to 11' Stairway Ladder Height = 3' to 5' Scaffold Position Height = 1' to 2' Weight = 27.5 lbs. 	AA
494M34	17 FT	Werner FMT-17	 Stepladder Height = 4' to 7' Extension Ladder Height = 9' to 15' Stairway Ladder Height = 4' to 7' Scaffold Position Height = 1' to 3' Weight = 35.1 lbs. 	
494M35	22 FT	Werner FMT-22	 Stepladder Height = 5' to 9' Extension Ladder Height = 11' to 19' Stairway Ladder Height = 5' to 9' Scaffold Position Height = 1' to 4' Weight = 45.6 lbs. 	



FIREDGIASS 3-SECTION COMPACT EXTENSION LADDEDS

LIBER	FIBERGLASS 3-SECTION COMPACT EXTENSION LADDERS			
ANSI IA Load Capacity: 300 lbs			D6200-3 SERIES FIBERGLASS COMPACT EXTENSION LADDER Innovative 3 section design reduces to shorter than standard 2 to maneuver and carry around. Easy to transport on top of vehi Twist-Proof® performance. Spring locks operate smoothly. Shoe spur plate. Retainer strap secures ladder for storage and transp. Note: 16' Item 22E977 is not equipped with rope and pulley.	section design. Convenient cles. ALFLO® rung joints for with slip-resistant pad and
22E977	16 FT	Werner D6216-3	Ladder Height 16', Total Length of sections 18', Maximum Working Length 13', Approx. shipping weight 40.5 lbs.	A
22E978	20 FT	Werner D6220-3	Ladder Height 20', Total Length of sections 23', Maximum Working Length 17', Approx. shipping weight 54 lbs.	
22E979	24 FT	Werner D6224-3	Ladder Height 24', Total Length of sections 27', Maximum Working Length 21', Approx. shipping weight 61.0 lbs.	
22E980	28 FT	Werner D6228-3	Ladder Height 28', Total Length of sections 31', Maximum Working Length 25', Approx. shipping weight 74.5 lbs.	
22E981	32 FT	Werner D6232-3	Ladder Height 32', Total Length of sections 35', Maximum Working Length 29', Approx. shipping weight 81 lbs.	H.



Grainger | Height | Model # Description

FIBERGLASS STRAIGHT LADDERS

ANSI IA Load Capacity: 300 lbs		•	D6200-1 SERIES FIBERGLASS STRAIGHT LADDERS ALFLO® rung joint means Twist-Proof® performance. Slip-resistant Traction-Tred® roungs. Double rail shield bracket and shoe with Shu-Lok® slip-resistant pad and spur p	
2EJG2	8 FT	Werner D6208-1	Ladder Height 8', Base Width 19", Approx. Shipping Weight 19.5 lbs.	
2EJG3	10 FT	Werner D6210-1	Ladder Height 10', Base Width 19", Approx. Shipping Weight 23.0 lbs.	
2EJG4	12 FT	Werner D6212-1	Ladder Height 12', Base Width 19", Approx. Shipping Weight 27.0 lbs.	
2EJG5	14 FT	Werner D6214-1	Ladder Height 14', Base Width 19", Approx. Shipping Weight 31.0 lbs.	
2EJG6	16 FT	Werner D6216-1	Ladder Height 16', Base Width 19", Approx. Shipping Weight 37.0 lbs.	
2EJG7	20 FT	Werner D6220-1	Ladder Height 20', Base Width 19", Approx. Shipping Weight 45.5 lbs.	

ALUMINUM STRAIGHT LADDERS

ANSI IA Load Capacity: 300 lbs			D1500-1 SERIES SINGLE LADDER Aluminum single ladders with ALFLO® direct rung-to-rai performance. Rugged shoe rests flat or is held in spur Ladder is constructed with I-beam rails and mar-resista	position with Shu-Lok® featur
3AZU7	8 FT	Werner D1508-1	Ladder Height 8', Approx. Shipping Weight 14.5 lbs. Base Width 18-1/8" outside rails	1.1
3AZU8	10 FT	Werner D1510-1	Ladder Height 10', Approx. Shipping Weight 17.5 lbs. Base Width 18-1/8" outside rails	
3AZU9	12 FT	Werner D1512-1	Ladder Height 12', Approx. Shipping Weight 21.5 lbs. Base Width 18-1/8" outside rails	
3AZV1	14 FT	Werner D1514-1	Ladder Height 14', Approx. Shipping Weight 27.0 lbs. Base Width 18-1/8" outside rails	-
3AZV2	16 FT	Werner D1516-1	Ladder Height 16', Approx. Shipping Weight 32.5 lbs. Base Width 18-1/8" outside rails	
3AZV3	18 FT	Werner D1518-1	Ladder Height 18', Approx. Shipping Weight 38.5 lbs. Base Width 18-1/8" outside rails	H

FIBERGLASS MANHOLE LADDERS

ANSI IA Load Capacity: 300 lbs		•	M7100 SERIES MANHOLE LADDER Fiberglass straight ladders 12" wide. ALFLO® direct rung-to-reperformance. Mar-resistant, vinyl coated aluminum hoop end manhole. 3' replaceable plastic sleeves to avoid manhole rim rail shield and shoe protects bottom of rail from damage.	caps for removing ladder from
3AZV4	8 FT	Werner M7108-1	Ladder Height 8', Approx. Shipping Weight 20.0 lbs. Base Width 12-3/8"	8.6
3AZV5	10 FT	Werner M7110-1	Ladder Height 10', Approx. Shipping Weight 24.0 lbs. Base Width 12-3/8"	H
3AZV6	12 FT	Werner M7112-1	Ladder Height 12', Approx. Shipping Weight 28.0 lbs. Base Width 12-3/8"	H
3AZV7	14 FT	Werner M7114-1	Ladder Height 14', Approx. Shipping Weight 32.0 lbs. Base Width 12-3/8"	H
3AZV8	16 FT	Werner M7116-1	Ladder Height 16', Approx. Shipping Weight 39.5 lbs. Base Width 12-3/8"	18



Grainger | Height | Model # | Description

STEP STOOLS

L	ANS oad Capac		ALUMINUM AND FIBERGLASS STEP STOOLS	
4XN38	2 FT	Werner 150B	Aluminum Step Stool Large molded top provides large standing platform. Molded vinyl foot pads riveted to rail. Spread 19". Width 17". Approx. Shipping Weight 5.5 lbs.	周
3AZU6	2 FT	Werner 6202	Fiberglass Step Stool Large molded top provides large standing platform. Combination rail end shield and foot with slip-resistant foot pad. Spread is 19-1/2". Width 17-1/4". Approx. Shipping Weight 9.0 lbs.	A A
4XP46	2 FT	Werner T372	Aluminum Twin Step Stool 300 lbs. Duty Rating (per side) Designed for one or two person jobs. Ideal for use with stage planks. Folds to 7- 1/4" Wide. Base Spread 23-3/8". Bottom Width 21-1/4". Approx. Shipping Weight 9.0 lbs.	AA
4XP47	2 FT	Werner T6202	Fiberglass Twin Step Stool 300 lbs. Duty Rating (per side) Designed for one or two person jobs. Ideal for use with stage planks. Folds to 7 1/2" Wide. Base Spread 23-3/8", Bottom Width 21-1/4". Approx. Shipping Weight 11.5 lbs.	
L	ANS oad Capac		AL400 SERIES STEP STOOL Aluminum Step Stool with comfortable tubular rails, slip-resis Easily transportable, ultra-lightweight, compact for easy stora intuitive, secure latch design enhance your stability when clim	ge. The soft comfort grip and
494H02	2 FT	Werner AL412-6	2 Steps. Platform Height 21". Platform size 15" x 12". Reach height 8'. Approx. Ship Weight 10 lbs., Base Spread 24", Bottom Width 18.5"	
494H03	3 FT	Werner AL413-6	3 Steps. Platform Height 30.5". Platform size 15" x 12". Reach height 9'. Approx. Ship Weight 13 lbs., Base Spread 30", Bottom Width 18.5"	

STEP STANDS

ANSI IAA Load Capacity: 375 lbs			ALUMINUM AND FIBERGLASS STEP STANDS Heavy duty 6" wide front rails and steps. Extra wide top. Spreade Extra large feet for use on gratings.	er bars lock permanently open.	
5W216	2 FT	Werner SSA02	Aluminum. Ladder Height 2', Approx. Shipping Weight 16.0 lbs. Base Spread 21", Bottom Width 17"		
6W705	3FT	Werner SSA03	Aluminum. Ladder Height 3'. Approx. Shipping Weight 21.0 lbs. Base Spread 27-1/2", Bottom Width 18-3/4"	1	
3LW39	22 FT	Werner SSF02	Fiberglass. Ladder Height 2'. Approx. Shipping Weight 15.0 lbs. Base Spread 21", Bottom Width 17"		
3LW40	33 FT	Werner SSF03	Fiberglass. Ladder Height 3'. Approx. Shipping Weight 19.5 lbs. Base Spread 27-1/2", Bottom Width 18-3/4"		



Grainger | Height | Model # | Description

PORTABLE WORK STANDS

ANSI IA Load Capacity: 300 lbs (per side)

ALUMINUM AND FIBERGLASS PORTABLE WORK STANDS


30" wide work stands with double wide top steps to provide wide platform. External Pinch-Proof™ spreaders for easy opening and closing. Mar-resistant feet for slip-resistance on concrete, wood and vinyl floors.

3AZU1	2 FT	Werner TW372-30	Aluminum. Ladder Height 2'. Approx. Shipping Weight 12.5 lbs. Base Spread 22", Bottom Width 23"
3AZU2	3 FT	Werner TW373-30	Aluminum. Ladder Height 3'. Approx. Shipping Weight 17.5 lbs. Base Spread 29", Bottom Width 34-3/4"



3AZU3	4 FT	Werner TW374-30	Aluminum. Ladder Height 4'. Approx. Shipping Weight 24.0 lbs. Base Spread 36", Bottom Width 36-1/2"







SCAFFOI DING

3 FT

Werner TW6203

3AZU5

	Aluminum and Steel Scaffolding				
4ZY17	4 FT	Werner PS-48	Rolling Portable Steel Scaffold Folds easily for storage and portability. Rolls easily on 4" non-marring hi-grade casters. Has 2 adjustable height planks. 500 lbs. Duty Rating (250 lbs. per plank).		
4XN62	6 FT	Werner 4101	Narrow Span 6' Adjustable Aluminum Base Section 6' Long x 29" Wide. Height adjusts from 6'6" to 7'6". Load Capacity 25 lbs. per square foot or 500 lbs. maximum per deck and scaffold. Includes walk board and 5" swivel locking casters.		
4XP11	6 FT	Werner 4110	Narrow Span 6' Aluminum Scaffold Guard Rail Section 6' Long x 29" Wide x 3-1/2' High.		



Grainger | Height | Model # | Description

SCAFFOLDING continued

12 FT

4XP22

Aluminum Scaffold Towers

12' HIGH ALUMINUM SCAFFOLD TOWER

6' Long x 29" Wide x 12' High Aluminum Scaffold Tower. Load Capacity 25 lbs. per square foot or 500 lbs. maximum per deck and scaffold. Includes walk board, 5" swivel locking casters, outriggers and toeboards.



15' HIGH ALUMINUM SCAFFOLD TOWER

4XP23 15 FT Werner GW402 6' Long x 29" Wide x 15' High Aluminum Scaffold Tower.

Load Capacity 25 lbs. per square foot or 500 lbs.

maximum per deck and scaffold. Includes walk board,

5" swivel locking casters, outriggers and toeboards.



4ZY18 20 Werner AP-20-MP6 Portable ar Standing L

Werner AP-30

Werner GW401

Aluminum Work Platform. 225 lbs. Load CapacityPortable and lightweight. Folds easily for storage. Highest Standing Level 20-9/16". Width 16-5/8", Length 40". Approx. Shipping Weight 75.0 lbs.(6)



Pro Deck Aluminum Platform. 300 lbs. Load Capacity

Extra large standing area with a rigid surface for working from side to side. The Pro Deck is ideal for working along walls and windows. Platform legs lock securely in place when in use and fold underneath platform for compact storage. The 300 lbs load capacity provides additional support for jobs requiring extra tools and supplies. Highest Standing Level 20-9/16". Width 16". Length 48". Approx. Shipping Weight 16.0 lbs.



PLANKS

36FX62

Inches

ANSI IA Load Capacity: 250 lbs (1 person)		bs (1 person)	ALUMINUM EXTENSION PLANKS Planks are 14" Wide. For use on stepladders, telescoping multiladders, extension trestle ladders, and extension and single ladders equipped with ladder jacks.	
4XP30	6 FT	Werner PA206	Closed Position 6' Long. Extended Position 9' Long. Approx. Shipping Weight 31.0 lbs.	_
4XP31	8 FT	Werner PA208	Closed Position 8' Long. Extended Position 13' Long. Approx. Shipping Weight 40.5 lbs.	
4XP32	10 FT	Werner PA210	Closed Position 10' Long. Extended Position 17' Long. Approx. Shipping Weight 56.5 lbs.	_



Grainger Height Model # Description

STAGES, HANDRAILS AND TOEBOARDS

ALUMINUM STAGE PLANKS, HANDRAILS AND TOEBOARDS

See Red 8 - 39 Book FT Varies by Size See Red Book **Aluminum Stage Planks**Ideal for ladder jack applications, swing stages, or catwalks. Strong design features double rungs on the ends for rigidity. Available in Lengths from 8' - 39' and Widths from 12" to 28". Load Capacity from 250 lbs.1-Man to 750 lbs. 3-Man. Vinyl-coated end caps.



See Red Book 8 - 39 FT

Varies by Size See Red Book Modular Guard Rail and Toe Board Systems

For use on Werner aluminum stage planks. Protects users and tools from falling off planks. Quick and easy to install, store and transport. Available in Lengths from 8' - 39' and Widths from 12" to 28". (Stage planks sold separately)



TRUCK RACK

Load Capacity: 1000 lbs		Steel Over Cab Pickup Truck Rack	
3AY77	Werner TR501-S	Black. Approx. Shipping Weight 125 lbs. Vinyl protector strips to protect equipment against transit damage. Includes adaptor plates that allow rack to mount over most cabs (750 lbs. load capacity). Includes quick release rear bar feature and predrilled uprights. Cargo positioners help protect cargo in transit.	

VAN RACK

Load Capacit	ty: 600 lbs	Steel Van Rack	
3AY76	Werner VR401-W	White. Approx. Shipping Weight 40 lbs. Includes predrilled uprights. Cargo positions and vinyl strips help protect cargo in transit.	

ACCESSORIES

ACCESSO		es designed to fit Werner ladders to increase productivity and safet	ty
458T05	Werner AC63	The Podium Gate attaches to any Werner Podium as a field install accessory providing 360 degrees of contact when standing on the top platform step. Gate easily swings open and locks closed when ascending and descending the ladder. Entire gate folds up for easy storage. Great for all trades. Approx. Ship Weight 6 lbs.	



Grainger Height Model # Description

Werner AC50-JB-3

Werner AC58-TL

ACCESSORIES

1XGF7

1XGF8

4XN88

4XN82

4ZY21

4XN81

Accessories designed to fit Werner ladders to increase productivity and safety

JobBucket Accessory, 25 lbs. Load Capacity.

Compatible with OBEL00, OBCN00, 6200 Series and 6000 Series. Increase ladder storage and maximize your work space on top of your ladder. Over 600 cubic inch capacity. Shipped in boxes of 3.





ToolLasso® with Belt Clip Accessory

Secures tools from falling. Can be wrapped around the grip of power tools, hand tools or caulk guns. Keeps tools within easy reach on top of your ladder or on a belt. Clip

attaches to belt and ToolLasso® fits into belt clip.



4XN86 Werner AC19-2

Extension Ladder Covers

Helps protect surfaces from scratches and dents. Flexible and easy to install. Made of soft rubber material.



QuickClick™ Stabilizer

Werner AC78 Stabilizer with spring-loaded locking latch makes it easier to install and remove than conventional stabilizers.

Modular 3 component design allows for compact storage.

Spans 44" and stands off 10".



Aluminum Ladder Jacks

Lightweight, sturdy and easy to use. Accepts planks up to 20" wide. Platform clamps secure entire ladder jack system. Jack mounts on either side of extension ladder. For

tem. Jack mounts on either side of extension ladder. For use on ladders of 250 lbs., Type I Duty Rating or higher.





Aluminum Ladder Leveler

Werner PK70-1

Allows use on uneven surfaces and adjusts up to 8-1/2". Ladder Leveler with 2 base attachments. Base unit stays attached while leveler can be easily removed when not in use. Use on either side of ladder. For Werner extension

,a a

Stabilizer and Surface Protector

Span adjustment is 49", 57" or 65". Stand-off distance is 12" or 29-1/2". Rectangular stabilizer spans double windows. Quickly converts stand off distance for larger overhangs. Mounts quickly and easily. Comes with rubber

pads and fleece bonnets.

ladders only.

NOTE: SEE RED BOOK FOR ADDITIONAL ITEMS AND INFORMATION

Werner 97P



www.wernerco.com

For more information contact your Grainger Representative or visit Grainger.com®

