

# Streamvault SV-2000E

# Turnkey security appliance

The Streamvault™ SV-2000E security appliance is a turnkey solution that lets you easily deploy a unified system combining video surveillance, access control, automatic license plate recognition and communications. It accelerates your project by delivering a secure appliance with Security Center pre-loaded.

Guaranteed performance

up to
> 2480 Mbps
total throughput

up to
> 2000
readers

up to up to **288**ALPR cameras NLSA

> 288 TB NLSAS storage

# **Key features**

Turnkey appliance with Genetec™ Security Center pre-installed

Video surveillance-grade NLSAS storage with RAID 5, 6 or 10 configuration

iDRAC9 Enterprise for local and remote server management

Machine learning endpoint protection

5-year hardware warranty with Keep Your Hard Drive and nextbusiness day on-site service



# **Benefits**



Design with confidence – The SV-2000E appliance is delivers certified performance for a wide range of scenarios, so you know your system will meet your needs today and tomorrow.



Protect your security system –
Streamvault appliances help you build a resilient security system that protects

your data and operations. Our cyber security experts stay vigilant on evolving threats and help identify and address new vulnerabilities promptly.



**Get up and running faster** – The SV-2000E appliance is ready to install the moment you receive it. It shortens deployment time and standardizes processes across locations.

# **Applications**

#### **Education**

Provide a safer environment for students and staff across your campus, or deploy the SV-2000E appliance as a centralized monitoring solution for multiple remote schools.

## **Transportation**

Take advantage of advanced security capabilities, such as dyamic mapping and video analytics, and help your team efficiently monitor and respond to events across your terminal.

#### Retail

The SV-2000E appliance lets you standardize security processes across your entire chain. Augment video surveillance with ALPR and point-of-sale integration to make the most of your system.



# Technical specifications

#### OS

Windows Server 2022

#### **Processor**

SV-2040E-R4/R6S: 1x Intel® Xeon® E-2436 Passmark: 22,775 SV-2040E-R15:

1x Intel® Xeon® Silver 4416+ 2.0GHz

Passmark: 44,140

# Memory

32GB DDR5

#### **Ethernet**

SV-2040-R4/R6S: 2x 1GbE RJ45

SV-2040-R15: 2x 1GbE RJ45, 2x 10/25GbE

SFP28

## **Peripherals**

1x USB 2.0 + 1x USB 3.0

# Video output

1x VGA

# Remote Management

iDRAC9 Enterprise

## **Performance**

SV-2040E-R4/R6S: 930 Mbps / 300

cameras

SV-2040E-R15: 2480 Mbps / 800 cameras

# Mechanical and environmental

## Operating temperature

50°F to 95°F (10°C to 35°C)

# **Operating humidity**

8 - 80% (non-condensing)

## Expansion

SV-2040E-R4/R6S: 2x PCIe LP slots SV-2040E-R15: Up to 2x PCIe LP slots

# Cybersecurity

# **Endpoint protection**

Arctic Wolf Aurora Protect machine learning antivirus

### Hardened image

200+ security setting changed by default

# Maintenance

Verified Windows updates
Connected services for Genetec software
and device firmware updates

# **Storage**

# **Drive type**

Enterprise HDD (hot-swappable)

#### OS drive

SV-2040E-R4/R6S: 2x 480GB SSD

RAID 1 (hot-swappable)

SV-2040E-R15: 2x 480GB M.2 NVMe RAID

1 (hot-swappable)

## Available drive sizes

12TB, 16TB, 20, 24TB

#### **RAID** controller

SV-2040E-R4: H755 8GB NV cache

SV-2040E-R6S: H355

SV-2040E-R15: H755 8GB NV cache

#### **Data RAID level**

SV-2040E-R6S: RAID 1

SV-2040E-R4/R15: RAID 5 or 6, RAID 10

available as an option

## Maximum data storage

SV-2040E-R4/R6S: 80TB (raw), 59.88TB

(usable)

SV-2040E-R15: 360TB (raw); 311 TB (usable)

# Warranty and support

#### Hardware warranty

5-year hardware warranty with Keep Your Drive and next business day on-site service

### **Security Center support**

All general availability, restricted availabilty, and extended maintenance versions

# Models

| Model           | Form factor | Bays                           | Dimensions (W x D x H)                               | Max weight           | Power (100-240v) |
|-----------------|-------------|--------------------------------|--|----------------------|------------------|
| SV-2040E-R4/R6S | 1U          | Up to 6x 2.5"<br>Up to 4x 3.5" | 19" x 20.43" x 1.685"<br>(482mm x 518.82mm x 42.8mm) | 29.17 lbs (13.23 kg) | 2x 600W          |
| SV-2040E-R15    | 2U          | 15                             | 17.1" x 28.2" x 3.4"<br>(434mm x 716mm x 87mm)       | 69.58 lbs (31.56 kg) | 2x 1100W         |